Geolocation validation of CERES instruments using radiance measurements

Peter Spence^a, Phillip Hess^a, Kory Priestley^b
^aScience Applications International Corporation (SAIC)
^bAtmospheric Sciences, NASA Langley Research Center

SPIE International Symposium on Optical Science and Technology, 03-08 August 2003, San Diego, California





Outline of Talk

- Coastline Detection Concept
- Error Analysis
- Results
- Conclusions





CERES Instruments

- 5 Instruments on 3 Satellite Platforms
 - TRMM (PFM) (no longer operational)
 - Terra (FM1, FM2)
 - Aqua (FM3, FM4)
- 3 Sensors per instrument

- Shortwave (0.3 μ m - 5.0 μ m)

- Window (8.0 μ m - 12.0 μ m)

- Total (0.3 μ m - >100 μ m)






Coastline Detection Concept

- During limb-to-limb scans:
 - Detect clear sky hot/cold radiance gradients provided by land-water boundaries (coastlines)
 - Determine corresponding geodetic coordinates
- Compare with digital coastline map
- Calculate along-track and cross-track distance errors.






Scanning Operations









• Fit a cubic to a contiguous set of 4 points.


 Find inflection point (e.g. 2nd derivative = 0).

 Inflection points between point 2 and 3 to represent sharp transitions or coastlines.









 Groups of N nearly contiguous points represent a coastline segment.

 Each coastline segment represents one sample in the analysis.






Error Analyses

- Compares computed coordinates with digital coastline map coordinates using Amoeba Error Analysis.
- Adjusts using downhill simplex minimization algorithm to minimize rms angular map crossing distances.
- Derives along-track and cross-track distances.
- Classify detected scenes:
 - Inflection points within 20km of digital map.
 - Inflection thresholds [>10 w-m⁻²sr⁻¹day, >2 w-m⁻²sr⁻¹night]
 - +/-70⁰ latitude.








- Calculate distances to nearest map points (error).
- Shift data points up/down and left/right, calculate error.
 Iterate until error is minimized.
- Translate latitude and longitude errors to along-track and cross-track errors.
- Plot along-track and crosstrack errors on a scatter diagram.





Terra/CERES Coastline Detection 28 February 2000, Error Analysis







Results (Scatter Diagram)

Terra (3 year period):

– FM1 Along-track : ~1.1 km Aft

Cross-track: ~0 km

– FM2 Along-track : ~0.5 km Aft

Cross-track: ~1.5 km Lag

Aqua (1 year period):

– FM3 Along-track : ~0.8 km Aft

Cross-track: ~1.4 km Lead


– FM4 Along-track : ~0.1 km Lead

Cross-track: ~0.5 km Lag





Results (Scatter Diagram)



• Terra (3 year period):

– FM1 Along-track : ~1.1 km Aft


Cross-track: ~0 km

– FM2 Along-track : ~0.5 km Aft

Cross-track: ~1.5 km Lag












Results (Scatter Diagram)



Aqua (1 year period):

– FM3 Along-track : ~0.8 km Aft

Cross-track: ~1.4 km Lead


FM4 Along-track : ~0.1 km Lead

Cross-track: ~0.5 km Lag





Aqua Coastline Errors







Results (Trending)

• Terra (3 year period):

- FM1 Along-track : ~1.1 +/- 0.7 km Aft

Cross-track: ~0 +/- 0.4 km

Radius: ~1.2 +/- 0.7 km

- FM2 Along-track : ~0.5 +/- 0.9 km Aft

Cross-track: ~1.5 +/- 0.8 km Lag

Radius: ~1.9 +/- 0.4 km





Results (Trending)

Aqua (1 year period):

- FM3 Along-track : ~0.8 +/- 0.2 km Aft

Cross-track: ~1.4 +/- 0.7 km Lead

Radius: ~1.7 +/- 0.5 km

– FM4 Along-track : ~0.1 +/- 0.2 km Lead


Cross-track: ~0.5 +/- 0.5 km Lag

Radius: $\sim 0.7 + / - 0.4 \text{ km}$





Terra Results (3 Year Trending)



FM1:

– Along-track : ~1.1 +/- 0.7 km Aft

Cross-track: ~0 +/- 0.4 km

– Radius: ~1.2 +/- 0.7 km

FM2:

– Along-track : ~0.5 +/- 0.9 km Aft


Cross-track: ~1.5 +/- 0.8 km Lag

– Radius: ~1.9 +/- 0.4 km






Terra Coastline Errors Trend







Aqua Results (1 Year Trending)



FM3:

– Along-track : ~0.8 +/- 0.2 km Aft

Cross-track: ~1.4 +/- 0.7 km Lead

– Radius: ~1.7 +/- 0.5 km

FM4:

Along-track : ~0.1 +/- 0.2 km Lead


Cross-track: ~0.5 +/- 0.5 km Lag

– Radius: ~0.7 +/- 0.4 km





Aqua Coastline Errors Trend







Conclusions

- Automated coastline detection a valuable tool to validate pointing accuracy and knowledge.
- Pointing errors shown to be <10% of CERES 20 km footprint on both the Terra and Aqua spacecrafts.
- Trends continue to indicate nominal pointing stability over time.





Backup Slides






Coastline Detection

- Automated coastline detection
- Analyzed 20 FM1 scenes, 18 FM2 scenes occurring on 28 February 2000
- Initial results indicate low navigational errors for both instruments





Terra/CERES Coastline Detection 28 February 2000, 20 km Square Search




 Groups of N nearly contiguous points represent a coastline segment.

 Each coastline segment represents one sample in the analysis.






Terra/CERES Coastline Detection 28 February 2000, 20 km Square Search







Terra/CERES Coastline Detection 28 February 2000, Descending, 08:10:00 - 08:20:00 UT







Terra/CERES Coastline Detection 28 February 2000, Error Analysis

